

CavityTherm[®]

Built-in Full Fill Wall Insulation

CT/PIR

Insulation for
Full Fill Cavity-Wall Corner Panel

The built in full fill cavity wall insulation shall be Xtratherm Thin-R CavityTherm CT/PIR manufactured to EN 13165 by Xtratherm, including corner boards and ancillary detail components, comprising a rigid Polyisocyanurate (PIR) core between low emissivity foil facings with engineered HIPS outer skin. The CT/PIR_ _ _mm with a Agrément declared Lambda value of 0.021 W/mK to achieve a U value of _ _ _W/m²K for the wall element. To be installed in accordance with instructions issued by Xtratherm.

Refer to NBS clause F30 150, F30 12

Insulation

Polyisocyanurate Rigid Foam

Standard

BS EN 13165

Certification

BBA Certification No. 10/4786. Issue date: 31 March 2011
BS EN ISO 9001 Quality Management System
BS EN ISO 14001 Environmental Management System

Manufacturer

Xtratherm UK Limited

Holmewood Industrial Park, Holmewood
Chesterfield, Derbyshire, S42 5UY

T + 44 (0) 371 222 1033

F + 44 (0) 371 222 1044

info@xtratherm.com

www.xtratherm.com

Xtratherm Limited

Liscarton Industrial Estate, Kells Road,
Navan, Co.Meath, Ireland, C15NP79

T +353 (0)46 906 6000

F +353 (0)46 906 6090

info@xtratherm.ie

www.xtratherm.ie

Face size

1200 x 450 mm

Edge profile

Rebated all four edges

Thickness

75 mm / 90 mm / 100 mm / 125 mm /
150mm

Product reference

Xtratherm Thin-R CT/PIR Full Fill
Cavity Wall Insulation

Other sizes available dependent on quantity & lead time.