

Safe-R

Superior Performance
Phenolic Insulation

SR/TB

Insulation for Dry Lining Walls Fixed with
Adhesive Dabs

The insulated drylining wall insulation shall be Xtratherm Safe-R SR/TB manufactured to EN 13950 by Xtratherm, comprising a rigid Phenolic core between composite glass tissue/foil facings. The SR/TB_ _ _mm with Lambda value as low as 0.020 W/mK (Phenolic only), bonded to 12.5mm plasterboard, to achieve a U value of _ _ _W/m²K for the wall element. To be installed in accordance with instructions issued by Xtratherm.

Refer to NBS clause K10 205, K10 15

Insulation

Phenolic Rigid Foam

Standard

BS EN 13950

Certification

BS EN ISO 9001 Quality Management System
BS EN ISO 14001 Environmental Management System

Manufacturer

Xtratherm UK Limited

Holmewood Industrial Park, Holmewood
Chesterfield, Derbyshire, S42 5UY

T + 44 (0) 371 222 1033

F + 44 (0) 371 222 1044

info@xtratherm.com

www.xtratherm.com

Face size

2400 x 1200 mm

Thickness

25mm / 40mm / 50mm / 60mm / 75mm /
80mm / 100mm

Edge profile

Plasterboard - Tapered
Phenolic - Square Edge

Product reference

Xtratherm Safe-R SR/TB
Thermal Liner Insulation

Other sizes available dependent on quantity & lead time.