

Safe-R

Superior Performance
Phenolic Insulation

SR/RS

Insulation for
Ventilated Rainscreen Cladding

The rainscreen insulation shall be Xtratherm Safe-R SR/RS ___mm manufactured to EN 13166 by Xtratherm, comprising a rigid Phenolic core. The SR/RS ___mm with Agrément declared Lambda value as low as 0.020W/mK to achieve a U value of ___W/m²K for the wall element. To be installed in accordance with instructions issued by Xtratherm.

Refer to NBS clause M21 210, M21 220

Insulation

Phenolic Rigid Foam

Standard

BS EN 13166

Certification

BS EN ISO 9001 Quality Management System
BS EN ISO 14001 Environmental Management System

Manufacturer

Xtratherm UK Limited

Holmewood Industrial Park, Holmewood
Chesterfield, Derbyshire, S42 5UY

T + 44 (0) 371 222 1033

F + 44 (0) 371 222 1044

info@xtratherm.com

www.xtratherm.com

Face size

2400 x 1200 mm

Edge profile

Straight Edge

Thickness

50mm / 60mm / 75mm / 80mm / 90mm /
100mm / 120mm

Product reference

Xtratherm Safe-R SR/RS
Rainscreen Insulation

Other sizes available dependent on quantity & lead time.