

XtroLiner

Superior Performance PIR Insulation

XO/FB

Insulation for
Steel & Timber Frame Systems

The wall insulation shall be Xtratherm XtroLiner XO/FB manufactured to EN 13165 by Xtratherm, comprising a rigid modified Polyisocyanurate (PIR) core with textured robust low emissivity foil facings. The XO/FB_ _ _mm with a Agrément declared Lambda value of 0.021 W/mK to achieve a U value of _ _ _W/m2K for the wall element. To be installed in accordance with instructions issued by Xtratherm.

Refer to NBS clause F30 12, F30 155, K10 15, K10 205

Insulation

Modified Polyisocyanurate Rigid Foam

Standard

BS EN 13165

Certification

BS EN ISO 9001 Quality Management System
BS EN ISO 14001 Environmental Management System

Manufacturer

Xtratherm UK Limited

Holmewood Industrial Park, Holmewood
Chesterfield, Derbyshire, S42 5UY

T + 44 (0) 371 222 1033

F + 44 (0) 371 222 1044

info@xtratherm.comwww.xtratherm.com

Xtratherm Limited

Liscarton Industrial Estate, Kells Road,
Navan, Co.Meath, Ireland, C15NP79

T +353 (0)46 906 6000

F +353 (0)46 906 6090

info@xtratherm.iewww.xtratherm.ie

Face size

2400 x 1200 mm

Edge profile

Straight Edge

Thickness

50mm / 60mm / 75mm / 80mm /
100mm / 120mm

Product reference

Xtratherm XtroLiner XO/FB
Steel & Timber Frame Insulation

Other sizes available dependent on quantity & lead time.