

CavityTherm[®]

Built-in Full Fill Wall Insulation

CT/PIR

Thin-R CavityTherm Service Void

The Service Void insulation shall be Xtratherm Thin-R 50mm thick, 250mm width and 450mm depth, manufactured to EN 13165 by Xtratherm, comprising a rigid Polyisocyanurate (PIR) core between low emissivity foil facings, with a Agrément declared Lambda value of 0.021 W/mK, creating a preformed panel for an insulated Service Void in _ _ _mm cavity. To be installed in accordance with instructions issued by Xtratherm.

Refer to NBS clause F30 12, F30 155

Insulation

Polyisocyanurate Rigid Foam

Standard

BS EN 13165

Certification

BS EN ISO 9001 Quality Management System
BS EN ISO 14001 Environmental Management System
BS OHSAS 18001 Health and Safety Management System

Manufacturer

Xtratherm UK Limited

Holmewood Industrial Park, Holmewood
Chesterfield, Derbyshire, S42 5UY

T + 44 (0) 371 222 1033

F + 44 (0) 371 222 1044

info@xtratherm.com

www.xtratherm.com

Xtratherm Limited

Liscarton Industrial Estate, Kells Road,
Navan, Co.Meath, Ireland, C15NP79

T +353 (0)46 906 6000

F +353 (0)46 906 6090

info@xtratherm.ie

www.xtratherm.ie

Product reference

Xtratherm Thin-R Service Void
Insulation.