

CavityTherm[®]

Built-in Full Fill Wall Insulation

CT/PIR

Full Fill Cavity-Wall Top Panel

The built-in full fill cavity wall Top Panel insulation shall be Xtratherm Thin-R CavityTherm CT/TP manufactured to EN 13165 by Xtratherm, including corner boards and ancillary detail components, comprising a rigid Polyisocyanurate (PIR) core between low emissivity foil facings with engineered HIPS outer skin. The CT/TP_ _ _mm with a Agrément declared Lambda value of 0.021 W/mK to achieve a U value of _ _ _W/m²K for the wall element. To be installed in accordance with instructions issued by Xtratherm.

Refer to NBS clause F30 151, F30 12

Insulation

Polyisocyanurate Rigid Foam

Standard

BS EN 13165

Certification

BBA Certification No. 10/4786.

Issue date: 31 March 2011

BS EN ISO 9001 Quality Management System

BS EN ISO 14001 Environmental Management System

BS OHSAS 18001 Health and Safety Management System

Manufacturer**Xtratherm UK Limited**Holmewood Industrial Park, Holmewood
Chesterfield, Derbyshire, S42 5UY

T + 44 (0) 371 222 1033

F + 44 (0) 371 222 1044

info@xtratherm.comwww.xtratherm.com**Xtratherm Limited**Liscarton Industrial Estate, Kells Road,
Navan, Co.Meath, Ireland, C15NP79

T +353 (0)46 906 6000

F +353 (0)46 906 6090

info@xtratherm.iewww.xtratherm.ie**Face size**

1200 x 225 mm

Edge profile

Rebated all four edges

Thickness

100 mm / 125 mm / 150mm

Product referenceXtratherm Thin-R CT/TP Full Fill
Cavity Wall Top Panel Insulation.