

## Cavity Wall 360

## ECO/CW

### Partial Fill Wall Insulation

The partial fill cavity wall insulation shall be Xtratherm Cavity Wall 360 manufactured to EN 13165 by Xtratherm, comprising of a rigid modified Polyisocyanurate (PIR) core with textured robust low emissivity foil facings and engineered shiplapped jointing. Cavity Wall 360\_ \_mm with a Lambda value of 0.020 W/mK to achieve a U-Value of \_ \_ W/m<sup>2</sup>K for the wall element.

To be installed in accordance with instructions issued by Xtratherm.

#### Insulation

Polyisocyanurate Rigid Foam

#### Standard

BS EN 13165

#### Manufacturer

##### Xtratherm UK Limited

Holmewood Industrial Park, Holmewood  
Chesterfield, Derbyshire, S42 5UY

T + 44 (0) 371 222 1033

F + 44 (0) 371 222 1044

[info@xtratherm.com](mailto:info@xtratherm.com)

[www.xtratherm.com](http://www.xtratherm.com)

##### Xtratherm Limited

Liscarton Industrial Estate, Kells Road,  
Navan, Co.Meath, Ireland, C15NP79

T +353 (0)46 906 6000

F +353 (0)46 906 6090

[info@xtratherm.com](mailto:info@xtratherm.com)

[www.xtratherm.com](http://www.xtratherm.com)

#### Thickness

100mm /110mm

#### Edge profile

Shiplap

#### Product reference

Xtratherm  
Cavity Wall 360 Partial Fill  
Wall Insulation